

SIEMENS

Product data sheet

4AM4642-4TN00-0EA0



TRANSFORMER SITAS;
 PHASES:1;
 PN/PN(S6)(KVA):0,4 /1,44;
 UPRI(V):230+/-5%;
 USEC(V):24;
 ISEC(A):16,7;
 F(HZ):50...60;
 VECTOR GR./SHIELD WNG.:li0 /0;
 TA/ISOKL:40 /B;
 IP00;
 TYPE OF TERMINALS:SCREW/TAB CONNECTION;
 INSTALLATION:SCREW;
 EN 61558-2-2,
 -2-6 >CONTROL CIRCUIT TRANSFORMER<
 >SAFETY ISOLATING TRANSFORMER<

General technical details:

Product designation	transformer SITAS
Product brand name	SIDAC
Operating apparent output / rated value	400 VA
Efficiency	0.91
Manner of switching for transformers	li0
varification of suitability	CE / cRUus
Product function	
<ul style="list-style-type: none"> • Temperature surveillance • Isolation control • Short circuit and overload protection 	<p>No</p> <p>No</p> <p>No</p>
Number of the protective coils	0
Short-term vector power	1440 VA
Relative short-circuit voltage	4.4 %
Inputs:	
Phase number / of the inputs	1
Input voltage	

• _1 / rated value	242 V
• _2 / rated value	230 V
• _3 / rated value	218 V
Electrical input frequency	
• minimum	50 Hz
• maximum	60 Hz
Outputs:	
Phase number / of the outputs	1
Output voltage	
• _1 / rated value	24 V
Electrical output frequency	
• maximum	60 Hz
• minimum	50 Hz
Ambient conditions:	
Thermal class / acc. to IEC 60085	B
Ambient temperature / rated value	40 °C
Protection class IP	IP00
Mechanical design:	
Design of the electrical connection	
• secondary side / for main current circuit	screw-type terminals / tab terminals
• at the input / for main current circuit	screw-type terminals / tab terminals
Type of fixing/fixation	screws
Construction form of the iron core	EI 120/52
Width	0.122 m
Height	0.121 m
Depth	0.114 m
last change:	12/01/2007

Technical Assistance:	Telephone:	+49 (0) 911-895-5900 (8°° - 17°° CET)
	Fax:	+49 (0) 911-895-5907
	E-Mail:	technical-assistance@siemens.com
	Internet:	www.siemens.de/lowvoltage/technical-assistance