



Special Equipment Test Equipment Detector Tester

Type	Order No.										
RG320	BPZ:5166880001										
	<p>Bellow for RE6</p> <p>The bellow is fitted to the RE6 to fit all SynoLINE300 point detectors in an ideal way.</p>										
RE6T	BPZ:3680270001										
	<p>Detector tester for heat detectors</p> <p>This detector tester contains a hot air generator. For the performance check, the tester is pushed over the detector. The hot air released, heats the detector and so actuates an alarm.</p> <p>Forbidden in electrical switching stations or areas where there is a danger of explosion!</p> <p>The extension rod FDUM291/292 must be ordered separately.</p> <table data-bbox="429 831 1086 1025"> <tr> <td>Mains voltage</td> <td>220 VAC/50... 60 Hz, ~300 W</td> </tr> <tr> <td>Operating temperature</td> <td>0... +40 °C</td> </tr> <tr> <td>Data sheet</td> <td>AlgoRex, Synova -> 001164 Sinteso -> 007228 Cerberus PRO -> A6V10203222</td> </tr> <tr> <td>Accessories</td> <td>FDUM291 Telescope rod FDUM292 Telescope rod</td> </tr> </table>	Mains voltage	220 VAC/50... 60 Hz, ~300 W	Operating temperature	0... +40 °C	Data sheet	AlgoRex, Synova -> 001164 Sinteso -> 007228 Cerberus PRO -> A6V10203222	Accessories	FDUM291 Telescope rod FDUM292 Telescope rod		
Mains voltage	220 VAC/50... 60 Hz, ~300 W										
Operating temperature	0... +40 °C										
Data sheet	AlgoRex, Synova -> 001164 Sinteso -> 007228 Cerberus PRO -> A6V10203222										
Accessories	FDUM291 Telescope rod FDUM292 Telescope rod										
RE7T	S54370-S3-A1										
	<p>Solo461 Heat detector tester kit</p> <p>The detector tester contains a hot air generator and is battery-powered. The detector tester will automatically start testing when infrared beam in cup is broken.</p> <p>Forbidden in electrical switching stations or areas where there is a danger of explosion!</p> <p>The adapter RE7T-A and the extension rod FDUM291/292 must be ordered separately.</p> <table data-bbox="429 1335 1086 1559"> <tr> <td>Relative humidity</td> <td>≤95 %</td> </tr> <tr> <td>Operating temperature</td> <td>5... +45 °C</td> </tr> <tr> <td>Storage temperature</td> <td>-10... +50 °C</td> </tr> <tr> <td>Data sheet</td> <td>A6V10252901</td> </tr> <tr> <td>Accessories</td> <td>RE7T-A Solo719 Adapter for FDUM29x FDUM291 Telescope rod FDUM292 Telescope rod</td> </tr> </table>	Relative humidity	≤95 %	Operating temperature	5... +45 °C	Storage temperature	-10... +50 °C	Data sheet	A6V10252901	Accessories	RE7T-A Solo719 Adapter for FDUM29x FDUM291 Telescope rod FDUM292 Telescope rod
Relative humidity	≤95 %										
Operating temperature	5... +45 °C										
Storage temperature	-10... +50 °C										
Data sheet	A6V10252901										
Accessories	RE7T-A Solo719 Adapter for FDUM29x FDUM291 Telescope rod FDUM292 Telescope rod										