



N 512/21 SWITCH ACTUATOR SUBMODULE 3XAC230V, 16A

Similar to image

Technical data:

| | | |
|---|---|-----------------------------|
| Type of display / LED | | No |
| Type of mounting | | modular installation device |
| Switching capacity real power | W | 3,680 |
| Breaking capacity current | A | 16 |
| Bus system / can be used / EIB/KNX | | No |
| Bus system / usable / RF bus system | | No |
| Bus system / usable / Powernet bus system | | No |
| Bus system / usable / LON bus system | | No |
| Number of pitch units for width | | 3 |
| Number of switching outputs / maximum | | 3 |
| Operating current / rated value | A | 16 |
| Operating voltage | | |
| • rated value | V | 230 ... 230 |
| Product function / direct operation | | Yes |
| Product component / integrated / Bus coupling | | No |
| Protection class IP | | IP20 |

Certificates/approvals:

General Product
Approval

Declaration of Conformity



GOST



EG-Konf.

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1512-1AB21/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1512-1AB21

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Jul 12, 2013