

BINARY OUTPUT RS 510/23 2X 10A,  
AC 230V (RELAY)



Similar to image

#### Technical data:

Type of display / LED		No
Type of mounting		modular installation device
Switching capacity real power	W	1,000
Breaking capacity current	A	10
Bus system / can be used / EIB/KNX		Yes
Bus system / usable / RF bus system		No
Bus system / usable / Powernet bus system		No
Bus system / usable / LON bus system		No
Number of switching outputs / maximum		2
Operating current / rated value	A	10
Operating voltage		
• rated value	V	230 ... 230
Product function / direct operation		No
Product component / integrated / Bus coupling		Yes
Protection class IP		IP20

#### Certificates/approvals:

## Declaration of Conformity



### Further information:

#### Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

#### Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

#### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/5WG1510-2AB23/all>

#### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5WG1510-2AB23](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5WG1510-2AB23)

#### CAX-Online-Generator

<http://www.siemens.com/cax>

#### Tender specifications

[Datanorm](#) [GAEB81](#) [GAEB83](#) [RTF](#) [TXT](#)

last change:

Jul 12, 2013