

# GM775LSNi

## SEISMIC DETECTOR

**VANDERBILT**



Vanderbilt's powerful GM7xx- series is the result of over 45 years engineering experience in the field of seismic detectors. Our products are specifically designed for round-the-clock monitoring of safes, ATMs, strong rooms or any other environment with high concentration of valuable assets or dangerous goods.

All known types of intruder attacks generate unique vibration patterns. Their characteristic values such as timing, frequency and amplitude are detected and analysed using Vanderbilt's patented Senstec® technology. This technology also ensures that environmental disturbances are ignored, and false alarms eliminated.

Even if you have a Local Security Network (LSN), you can take advantage of the protection offered by Vanderbilt's seismic detector range. The GM775LSNi is suited to use in LSNi and LSN bus systems for the effective protection of safes, night safes, ATMs, lightweight safes (LWS) and strong rooms.

### Key Features include:

- 5m operating radius / 80m<sup>2</sup> coverage area
- For applications on steel, concrete and lightweight, synthetic materials
- High performance Senstec® bimorph sensor for enhanced detection sensitivity
- Advanced micro-controller based digital signal processing
- Distinguishes reliably between real attacks and ambient noise
- Fast installation and adjustable application-specific sensitivity settings
- Remote-controlled sensitivity levels and response times via LSN
- Three operating modes: LSN classic, LSNi with automatic or manual addressing
- Small, slim and modern design
- Low power consumption

### Detection of:

- Hammers, chisels
- Saws, crowbars
- Sledgehammers
- Concrete grinders
- Diamond-head drills
- Hydraulic pressure tools
- Water-jet cutting tools
- Thermal tools
- Cutting torches
- Oxygen lances
- Explosives

### Immunity to:

- Operational noises
- Environmental influences

### Applications:

- Modular vaults
- Vaults with lightweight constructions
- ATMs armoured with synthetic materials
- Safes
- Night deposits

# GM775LSNi

## SEISMIC DETECTOR

**VANDERBILT**



## Features & Benefits

### ■ Reliable detection

Reliable recognition of all known mechanical and thermal attack tools, such as diamond-tipped drills, hydraulic pressure tools, flame cutters, thermal-lances or water jets on safes, automatic teller machines, night deposits, strong rooms and modular vaults made of steel.

### ■ Comprehensive Range

Vanderbilt's product range offers the right detector for every application, feature and approval requirement. For more information, visit [www.vanderbiltindustries.com](http://www.vanderbiltindustries.com).

### ■ Senstec® sensor

The patented Senstec® sensor and digital signal processing detects and evaluates a selected narrow frequency band to ensure reliable detection. This comprehensive protection is immune to environmental influences including air and structure borne noise from external disturbance sources.

### ■ Decades of experience

Vanderbilt has 45 years of engineering experience in protecting valuables in all aspects of security technology. Large-scale ongoing investment is dedicated to develop solutions and products for the very latest application.

### ■ LSN technology enabled

The GM775LSNi is designed to work with LSN Bus technology, which allows the detector and control panel to constantly exchange data. Hereby, the panel identifies, initialises and controls the GM775LSNi remotely. This means low-cost installation of the cable network, fast start-up, and easy maintenance.

## Recommended Accessories

### ■ Mounting plate

The use of the GMXP0 mounting plate ensures easy installation and reliable detection performance. It is strongly recommended to use the mounting plate on every Senstec® seismic detector and mandatory for use on uneven steel surfaces and concrete applications.

### ■ External test transmitter

The GMXS5 remote test transmitter is used to fully test and evaluate an installation with multiple detectors by simulating attack signals. If the seismic detectors are installed at the correct spacing and setting, the test signal is detected and an alarm is triggered.

### ■ Internal test transmitter

The GMXS1 remote test transmitter is installed directly inside the detector and is used for function and mounting testing of a single seismic detector prior to system arming.

**VANDERBILT**

# GM775LSNi

## SEISMIC DETECTOR

VANDERBILT



### ■ Technical Data

#### Detection characteristics

- Operating radius / Coverage area on concrete & steel
- For all types of tools (including thermal tools)

5m / 80m<sup>2</sup>

#### Power supply

$V_{\max} = 33V_{DC}$

#### Power consumption (8V<sub>DC</sub> ~ 16V<sub>DC</sub>)

- Quiescent / Alarm

$I_{typ} = 2.5mA \sim 3.5mA$   
 $I_{max} = 5mA$

#### Sabotage surveillance, Tamper

- Cover & surface contact
- Contact load

Opens on sabotage  
30V<sub>DC</sub> / 100mA

#### Test point output

Analogue integration signal

#### Function test

- Test duration until alarm with GMXS1
- Test duration until alarm with GMXS5

≤ 3s  
≤ 90s

#### Remote sensitivity reduction input

- For reduction
- Reduction to

Low ≤ 1.5V<sub>DC</sub> / High ≥ 3.5V<sub>DC</sub>  
50%, 25% or 12.5% of the original setting

#### Adjustments

- Configurations
- Modes selectable via LSNi/LSN control panels

LSN classic  
LSNi with automatic & manual addressing  
8 fixed modes  
1 freely programmable user mode

#### Environmental conditions

- Operating temperature
- Storage temperature
- Air humidity (EN 60721)
- Housing protection (EN 60529, EN 50102)
- Electromagnetic compatibility (EMC)

-40°C ~ 70°C  
-40°C ~ 70°C  
< 95%rh, non-condensing  
IP43  
EN 50130-4

#### Dimensions

89mm x 89mm x 22mm

#### Approvals

VdS Class C, VSÖ, BSI

VANDERBILT

# GM775LSNi

## SEISMIC DETECTOR

VANDERBILT

### ■ Ordering Information

Type	Art. No.	Description	Weight*
GM775LSNi	V54534-F114-A100	GM775LSNi Seismic detector	0.285kg
GMXP0	VBPZ:2772730001	GMXP0 Mounting plate - GM7xx	0.290kg
GMXC2	VBPZ:5021840001	GMXC2 Connection sleeve (16mm) - GM7xx	0.004kg
GMXS1	VBPZ:4202370001	GMXS1 Internal Test transmitter - GM7xx	0.025kg
GMXS5	VBPZ:5627000001	GMXS5 External Test transmitter - GM7xx	0.363kg
GMXB0	VBPZ:2772020001	GMXB0 Floor recess box - GM7xx	2.237kg
GMXW0	VBPZ:2771210001	GMXW0 Wall / Ceiling recess box - GM7xx	1.380kg
GMAS6	VBPZ:4886060001	GMAS6 Movable mounting kit - GM7xx	0.594kg
GMXP3	VBPZ:3470190001	GMXP3 Lock protection - GM7xx	0.780kg
GMXP3Z	VBPZ:5712410001	GMXP3Z Lock protection - GM7xx	0.823kg
GMXS2	VBPZ:3506110001	GMXS2 2mm Spacer for GMXP3 / GMXP3Z	0.014kg
GMXS4	VBPZ:3506240001	GMXS4 4mm Spacer for GMXP3 / GMXP3Z	0.025kg

\* Total weight of the product inclusive of the weight of its accessories and packaging.

VANDERBILT