

3-point spring return actuator with emergency function for adjusting air dampers in ventilation and air conditioning systems in buildings

- For air dampers up to approx. 2 m<sup>2</sup>
- Torque 10 Nm
- Nominal voltage AC 24 V
- Control: 3-point



## Technical data

<b>Electrical data</b>	Nominal voltage	AC 24 V, 50/60 Hz
	Nominal voltage range	AC 19.2 ... 28.8 V
	Power consumption	In operation 6.5 W @ nominal torque At rest 3 W For wire sizing 9 VA
	Connection	Cable 1 m, 4 x 0.75 mm <sup>2</sup>
<b>Functional data</b>	Torque Motor	Min. 10 Nm @ nominal voltage
	Spring return	Min. 10 Nm
	Direction of rotation Motor	Reversible with switch ↺ / ↻
	Spring return	Can be selected by mounting L / R
	Manual override	With hand crank and interlocking switch
	Angle of rotation	Max. 95°↺, can be limited with adjustable mechanical end stop
	Running time Motor	≤150 s (0 ... 10 Nm)
	Spring return	≤20 s @ -20 ... 50 °C / max. 60 s @ -30 °C
	Sound power level Motor	≤45 dB (A)
	Spring return	≤62 dB (A)
<b>Safety</b>	Service life	Min. 60,000 emergency positions
	Position indication	Mechanical
	Protection class	III Extra low voltage UL Class 2 Supply
	Degree of protection	IP54 NEMA2, UL Enclosure Type 2
	EMC	CE according to 2004/108/EC
	Certification	Certified to IEC/EN 60730-1 and IEC/EN 60730-2-14 cULus according to UL 60730-1A and UL 60730-2-14 and CAN/CSA E60730-1:02
	Mode of operation	Type 1.AA
	Rated impulse voltage	0.8 kV
	Control pollution degree	3
	Ambient temperature	-30 ... +50 °C
<b>Dimensions / Weight</b>	Non-operating temperature	-40 ... +80 °C
	Ambient humidity	95% r.h., non-condensating
	Maintenance	Maintenance-free
	Dimensions	See «Dimensions» on page 3
	Weight	Approx. 1.9 kg

## Safety notes



- The actuator is not allowed to be used outside the specified field of application, especially in aircraft or in any other airborne means of transport.
- It may only be installed by suitably trained personnel. Any legal regulations or regulations issued by authorities must be observed during installation.
- The device may only be opened at the manufacturer's site. It does not contain any parts that can be replaced or repaired by the user.
- The cable must not be removed from the device.
- When calculating the required torque, the specifications supplied by the damper manufacturers (cross-section, design, installation site), and the air flow conditions must be observed.
- The device contains electrical and electronic components and is not allowed to be disposed of as household refuse. All locally valid regulations and requirements must be observed.

## Product features


<b>Mode of operation</b>	The actuator moves the damper to the operating position at the same time as tensioning the return spring. The damper is turned back to the safety position by spring force if the supply voltage is interrupted. The actuator is controlled with a 3-point signal and moves the damper to the operating position at the same time as tensioning the return spring. The damper is turned back to the emergency position by spring force if the supply voltage is interrupted.
<b>Simple direct mounting</b>	Simple direct mounting on the damper spindle with a universal spindle clamp, supplied with an anti-rotation strap to prevent the actuator from rotating.
<b>Manual override</b>	Manual operation of the damper with the hand crank, locking in any position with the interlocking switch. Unlocking is manual or automatic by applying the operating voltage.
<b>Adjustable angle of rotation</b>	Adjustable angle of rotation with mechanical end stop.
<b>High operational reliability</b>	The actuator is overload-proof, requires no limit switches and automatically stops when the end stop is reached.

## Electrical installation

### Wiring diagram

#### Notes


- Connect via safety isolation transformer.
- Parallel connection of other actuators possible. Note the performance data.



#### Cable colours:

- 1 = black
- 2 = red
- 3 = white
- 4 = white

### Direction of rotation



## Accessories






	Description	Data sheet
<b>Electrical accessories</b>	Auxiliary switch unit S2A-F *	T2 - S2A-F
	Feedback potentiometer unit P200A-F *	T2 - P200A-F
<b>Mechanical accessories</b>	Various accessories	
	* further versions on request	

## Dimensions [mm]

### Dimensional drawings





Variant 1a:

$\frac{3}{4}$ "-spindle clamp (with insertion part) EU Standard

Damper spindle	Length			
	$\geq 85$	10 ... 22	10	14 ... 25.4
	$\geq 15$			





Variant 1b:

1"-spindle clamp (without insertion part) EU Standard

Damper spindle	Length		
	$\geq 85$	19 ... 25.4	12 ... 18
	$\geq 15$	(26.7)	

Variant 2:

$\frac{1}{2}$ "-spindle clamp (optional via configuration)

Damper spindle	Length		
	$\geq 85$	10 ... 19	14 ... 20
	$\geq 15$		

